on the selected size of data blocks 810_1 - 810_N (e.g., 8×8 , 4×4 having a larger N value or another grouping of elements). However, it is contemplated that the data set may comprise other types of data, as described above, without departing from the spirit and scope of the invention.

IN THE CLAIMS

1

3

5

7

8

1

2

3

Following is a complete set of claims as amended with this Response. This complete set of claims excludes cancelled claims 1 and 13-15, cancelled without prejudice, and includes revised claims 2-3 and 6.

1. Cancelled.

2. (Amended) The method of claim 6 further comprising:
repeatedly performing arithmetic operations on signal values associated with different
regions of the data set to produce a plurality of resultant signal values;
determining sign bits associated with the plurality of resultant signal values; and
providing the sign bits as the pseudo-random number sequence.

- 1 3. (Amended) The method of claim 6, wherein the generating of the pseudo-random number sequence comprises:
 - computing a mean signal value for a first region of the data set;
- 4 computing a mean signal value for a second region of the data set;
 - performing an arithmetic operation on the mean signal value of the first region and the mean signal value of the second region to produce a resultant signal value;
 - determining a sign bit of the resultant signal value; and providing the sign bit as a portion of the pseudo-random number sequence.
 - 4. The method of claim 3, wherein the performing of the arithmetic operation includes computing a difference between the mean signal value of the first region and the mean signal value of the second region.
- The method of claim 4, wherein each region of the data set includes a predefined image within the frame.

042390.P7032 App. No. 09/288,836 -2-

WWS/crr Filed: 4/8/99

1	\ 6.	(Amended) A method for improving detection of a watermark, comprising:
2	generating a pseudo-random sequence of numbers based on data associated with a data	
3	set;	
4	produ	cing the watermark by (i) computing a data block having an amplitude, (ii)
5	computing a secondary data set, each pixel of the secondary data set having a predetermined	
6	signal value, and (iii) multiplying the pseudo-random number sequence, the amplitude and the	
7	secondary data set to produce a result operating as the watermark; and	
8	embe	dding the watermark into the data set.
1	7.	The method of claim 6, wherein the amplitude for the watermark is computed
1/2	through adjustment of a plurality of parameters including frame differences.	
J		
1	8.	A method for extracting a watermark from a video sequence, comprising:
72	receiv	ring the video sequence having a first frame embedded with a watermark; and
3	recovering the watermark within the first frame through analysis of intensity differences	
4	between the first frame of the video sequence and a second frame of the video sequence.	
1	9.	The method of claim 8, wherein prior to recovering the watermark, the method
2	further comprises:	
3	comp	uting a pseudo-random number sequence using the random number generator seed.
•	10	
1	10.	The method of claim 9, wherein the recovering of the watermark includes:
2	computing a sum for products of (i) differences between watermarked intensities of the	
3	first frame and the second frame of the video sequence and (ii) corresponding elements of the	
4	pseudo-rando	om number sequence.
1	11.	The method of claim 10, wherein the recovering of the watermark further
2	includes:	
3	comp	uting a products of (i) a mean value for the differences between watermarked

pseudo-random number sequence.

4

5

intensities of the first frame and the second frame of the video sequence and (ii) a sum of the

100 1 4

6

7

12. The method of claim 11, wherein the recovering of the watermark further includes:

subtracting (i) the product of the mean value for the differences between watermarked intensities of the first frame and the second frame of the video sequence and the sum of the pseudo-random number sequence from (ii) the sum of products of the differences between watermarked intensities of the first frame and the second frame of the video sequence and the corresponding elements of the pseudo-random number sequence.

- 1 13. Cancelled.
- 1 14. Cancelled.
- 1 15. Cancelled.